

Fiest. Wireless



i3SYNC FHD 4.0 is a wireless and compact presentation tool that allows everyone to share their screen instantly. i3SYNC FHD 4.0 allows you to share your screen within a second without wires and without installation. It doesn't matter if you're using Windows, Apple or other operating systems, i3SYNC FHD 4.0 is OS independent and allows any HDMI device to share video and audio in high quality on a large screen.

Specifications

i3SYNC 4.0 Transmitter

PRODUCT INFORMATION

Model name	i3SYNC TX40-H
Size	60 mm x 60 mm x 20 mm (L x W x H)
Transmission Quality	Real time wireless mirroring Image: 1080P supported Sound: mono
Compatible devices	HDMI Devices: PC, tablets, camcorders and consoles, various smartphones (with adaptors)
Interface	HDMI 1.4, USB 2.0
Communication	802.11 b/g/n 2.4G 2T2R
Power Supply	Power via USB 5V 1A
Operating Range	up to 10 meters in open space
Operating Temperature	-5°C ~45°C
Operating Humid	20%~80% RH Non Condensation
Storage Temperature	-20°C ~ 60°C
Storage Humid	5%~93% RH Non Condensation

PACKAGE CONTENT

i3SYNC FHD HDMI TX 4.0	
installation manual	

OPTIONAL ACCESSORIES

i3ALLSYNC Storage

i3SYNC 4.0 Receiver

PRODUCT INFORMATION

Model name	i3SYNC RX40
Size	70 mm x 70 mm x 20 mm (L x W x H)
Receiver function	lmage: 1080P supported Sound: mono Automatic Recognition of transmitter
Compatible devices	HDMI Devices: PC, tablets, camcorders and consoles, various smartphones (with adaptors)
Interface	HDMI and micro USB
Communication	802.11 b/g/n 2.4GHz 2T2R
Power Supply	Uses external power supply over micro USB, 5V 1A

PACKAGE CONTENT

i3SYNC FHD HDMI TX 4.0
installation manual
Two antenna
Micro USB Cable
Universal Power adapter
HDMI cable (M-M) 120cm

CONTACT office@hauser

Tél.: 48.16.60

