





PACKAGE CONTENTS

- . USB 3.1 4K Camera
- . USB 3.1 type-C to type-A Cable (6ft) . Quick-start guide
- . Screws for tripod
- . Warranty card

CAMERA

- . Sensor: 1/2.5"Sony Exmor 4K CMOS sensor
- . Frame rate: 4K 30fps; 1080p , 720p , 960x540,
- 848x480, 800x448, 640x480, 640x360, 424x240, 320x240, 320x180 at up to 60fps
- . 120° Wide field of view
- . Lens iris, focus, zoom: fixed
- . AE, white balance: auto, manual override by PTZApp. Minimum working distance: 80 cm
- . Back light compensation and 2D noise reduction technology for optimizing light balance in different conditions
- . Standard tripod screw holes

ZOOM, PAN AND TILT MOVEMENT

- . Zoom: up to 4X leveraging 4K sensor (not available
- in 4K or 60 fps)
- . Pan and tilt: when zoom in leveraging 4K sensor

MICROPHONE

. 1 uni-directional microphones. Frequency response: 100~12K Hz. Sensitivity: -37dB

DIMENSIONS

- . Package dimensions: 138 x 138 x 149 mm . Package weight: 0.622 kg
- . Camera (folded): 60 x 60 x 75 mm
- . Camera weight: 0.251 kg

POWER SUPPLY

. Consumption: USB 3.1 supports up to 4K: 5V/0.9A; USB 2.0 Supports up to 2K: 5V/0.5A

60 mm

COMPATIBLE APPLICATIONS

ZOOM, Microsoft® Teams, Skype for Business, Skype™, Google Hangouts, Intel® Unite™, RingCentral, BlueJeans, V-Cube, LiveOn, CyberLink U Meeting®, TrueConf, Adobe Connect, Cisco WebEx®, Fuze, GoToMeeting™, Microsoft® Lync™, Vidyo, vMix, WebRTC, Wirecast, XSplit



Fit Everyone into Your Meeting

Obtain ultra-wide field of view video conferencing in your meeting room with a performance-quality multi-glass lens with deep focus and a staggering 120° FOV. Fit everyone at the table and the entire whiteboard into your meeting with minimal distortion.

No more awkward seating arrangements!



Freedom to Collaborate Anywhere

The CAM340+ is a completely portable solution for ultimate video conferencing convenience. With a versatile monitor mount, easy-to-carry size, and durable construction, the CAM340+ gives users the flexibility to make any room a huddle room.

FRONT



60 mm

SIDE



75 mm

BACK PANEL



USB 3.1